

IW200

Dual 8" In-Wall Subwoofer with
Sealed Enclosure



Specifications: IW200

Mounting hardware included

Nominal Impedance	4 Ohms
Frequency Response (1)	25 Hz - 160 Hz
Recommended Power	350 Watts
Transducer - Low Frequency Driver	(2x) 8" Mica-Graphite Polypropylene w/ NBR Surround
Colors	White
Enclosure alignment	Sealed
Grille - material	White Powder-Coated Galvanized Magnetic Micro-Flange (Paintable)
Height (SM = Height)	1828.8 mm / 72"
Diameter (SM = Width)	365.8 mm / 14.4"
Depth	86.36 mm / 3.4"
Cutout Height (Surface Mount Height)	520.7 mm / 20.5"
Cutout Width/Diameter	222.3 mm / 8.75"
Mounting Hole Diameter	Enclosure mounts between 16" on-center 2" x 4" studded wall
Mounting Depth	Enclosure mounts between 16" on-center 2" x 4" studded wall
Weight	27.2 kg / 60 lbs (Subwoofer and Back box)
Shipping Weight	29.5 kg / 65 lb
Regulatory - CE	approved
Regulatory - RoHS	approved

IW200

Dual 8" In-Wall Subwoofer with Sealed Enclosure



Description

Create deep, accurate bass without altering a room's design. Easily mount between standard wall studs. Contains patented subwoofer technology. Blend into any room's decor. Combine with the SolidDrive to create the ultimate "in-wall" home theater system.**

The IW-200 is an in-wall subwoofer with a sealed enclosure. The sub enclosure box mounts easily between 16" on-center wall studs, and its vibration-isolating outer foam layer virtually eliminates the risk of buzzing and wall rattling. Recommended for rooms up to 3,300 cubic feet in volume. Larger rooms can simply use multiple IW-200 subwoofers.

Features a 7-year warranty.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S.

and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase

Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Phase Technology

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax
Toll Free 8556635600
<http://phasetech.mseaudio.com>
All Phase Technologies products come with a 5-year limited warranty.

IW200

Dual 8" In-Wall Subwoofer with
Sealed Enclosure

