

---

# PC-Surround II

3-Way  
Switchable  
Bipole/Dipole  
Surround  
Speaker



## Specifications: PC-Surround II Mounting hardware included

Nominal Impedance	4 $\Omega$
Sensitivity dB @ 2.83V/1M	89 dB
Max. Continuous Power RMS	150 W
Recommended Power	20 - 150 Watts
Crossover Frequency	120 Hz; 2.5 kHz
Crossover Type	3-Way Absolute Phase®
Grille - material	Black Cloth or White Cloth
Height (SM = Height)	15.25"
Diameter (SM = Width)	14.5"
SM Depth (Including Bracket)	5.25"
Weight	19 lbs
Regulatory - CCC	approved

---

# PC-Surround II

3-Way  
Switchable  
Bipole/Dipole  
Surround  
Speaker



---

## Description

With a depth of only 5.5", the PC-Surround-II produces the all-important surround audio from a low-profile on-wall position. Switchable bipole and dipole modes allow for customizable home theater sound. The PC-Surround-II features a patented 6.5" tri-laminate Kevlar/RPF®/Glass Fiber flat-piston woofer, two 4" polypropylene midranges and two 1" soft dome tweeters.

## Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

## Technical Data and Specification Tools

### Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are

collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Phase Technology

8005 W. 110th St. | Suite 208  
Overland Park, KS 66210  
Phone 9136635600  
Fax  
Toll Free 8556635600  
<http://phasetech.mseaudio.com>  
All Phase Technologies products come with a 5-year limited warranty.