

# V62

## 2-Way Bookshelf Speaker



### Specifications: V62

### Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	88 dB
Frequency Response (1)	42 Hz - 20 kHz
Recommended Power	15 - 140 Watts
Crossover Frequency	2.2 kHz
Crossover Type	2-Way Absolute Phase®
Colors	Black Ash Vinyl
Enclosure alignment	Ported
Grille - material	Black Cloth
Height (SM = Height)	336.55 mm / 13.25"
Diameter (SM = Width)	209.55 mm / 8.25"
Depth	242.1 mm / 9.53"
Weight	4.8 kg / 10.5 lb
Shipping Weight	5.9 kg / 13.0 lb
Regulatory - RoHS	Approved

### Description

The V62 is large enough to be noticed but small enough to be placed just about anywhere. With its 6.5" VDT™ (Vapor Deposited Titanium) woofer and 1" woven synthetic soft dome tweeter, the V62 handles a wide range of frequencies at any volume.

For in-ceiling/in-wall options, pair the V62 with the [CS-6R](#), [CS-6R DVT](#), [CI6.0 IX QM Kit](#) or the [CI20X](#).

### Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

### Technical Data

### and Specification Tools

#### Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

#### Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs ([www.nwaalabs.com](http://www.nwaalabs.com)) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both

phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

### Architectural Specifications

No specifications currently.

#### Phase Technology

8005 W. 110th St. | Suite 208  
Overland Park, KS 66210  
Phone 9136635600  
Fax  
Toll Free 8556635600  
<http://phasetech.mseaudio.com>  
All Phase Technologies products come with a 5-year limited warranty.

---

# V62

2-Way Bookshelf Speaker

