



### Specifications: V626

### Mounting hardware included

|                                    |  |
|------------------------------------|--|
| Nominal Impedance                  | 8 ohms   |
| Sensitivity dB @ 2.83V/1M          | 89 dB  |
| Frequency Response (1)             | 32 Hz - 20 kHz                                       |
| Recommended Power                  | 15 - 200 Watts                                       |
| Transducer - Low Frequency Driver  | 6.5" VDT™ Vapor Deposited Titanium with NBR surround |
| Transducer - High Frequency Driver | 1" Patented Synthetic Soft Dome                      |
| Crossover Frequency                | 350 Hz; 2.2 kHz                                      |
| Crossover Type                     | 3-Way Absolute Phase®                                |
| Colors                             | Black Ash Laminate                                   |
| Enclosure alignment                | Ported   |
| Grille - material                  | Black Cloth  |
| Height (SM = Height)               | 1028.7 mm / 40.5"                                    |
| Diameter (SM = Width)              | 209.6 mm / 8.25"                                     |
| Depth                              | 242.1 mm / 9.53"                                     |
| Weight                             | 10.9 kg / 24 lb                                      |
| Shipping Weight                    | 14.1 kg / 31 lb                                      |
| Regulatory - CE                    | approved   |
| Regulatory - RoHS                  | approved   |

### Description

If bookshelf speakers aren't your thing, the V626 tower speaker gives any home entertainment system a majestic look and feel. Featuring two 6.5 Vapor Deposited Titanium (VDT™) woofers and a 1" woven synthetic soft dome tweeter, the V626 reproduces musical scores and movie soundtracks with stunning detail and clarity. A pair of V626s will frame a video display with its elegant black ash vinyl finish, enhancing a room's overall decor.

For in-ceiling/in-wall options, pair the V626 with the [CS-8R](#), [CI6.0 IX QM Kit](#) or the [CI20X](#).

### Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its

patents in order to protect Phase Technology resellers and end users.

### Technical Data and Specification Tools

#### Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

#### Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are

collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

### Architectural Specifications

No specifications currently.

#### Phase Technology

8005 W. 110th St. | Suite 208  
Overland Park, KS 66210  
Phone 9136635600  
Fax  
Toll Free 8556635600  
<http://phasetech.mseaudio.com>  
All Phase Technologies products come with a 5-year limited warranty.

---

# V626

3-Way Tower Speaker

