
CineMicro® Center

High Fidelity,
Ultra-Compact
Center Channel
Speaker



Specifications: CineMicro® Center Mounting hardware included

Nominal Impedance	8 Ω
Max. Continuous Power RMS	10 - 60 W
Crossover Frequency	4 kHz
Crossover Type	2-Way Absolute Phase®
Height (SM = Height)	4.25"
Diameter (SM = Width)	10.25"
SM Depth (Including Bracket)	4.75"
Weight	3.7 lbs
Shipping Weight	/ 4 lbs
Regulatory - CCC	approved

CineMicro® Center

High Fidelity,
Ultra-Compact
Center Channel
Speaker



Description

With its high-gloss, hand-polished piano black finish, the CineMicro® series offers a chic look and feel that goes well in any home. The acoustically neutral curved enclosures eliminate standing waves and provide greater rigidity, making these small speakers capable of extremely accurate and crisp sound reproduction.

The CineMicro Center features dual long-throw 3" polypropylene cone woofers with oversized motor structures and a ¾" dome tweeter that were designed for improved dialogue impact, functioning as both a center channel and as an LCR speaker. Also included is PhaseTech's Absolute Phase® Crossovers to expand the "sweet spot" both vertically and horizontally.

Designed with mounting ease and versatility, the CineMicro models utilize keyhole-style inserts on the backs make them easy to hang as well as self-adhesive bumpers attached to the bottoms to protect your surfaces from potential scratches.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots.

EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

CineMicro® Center

High Fidelity,
Ultra-Compact
Center Channel
Speaker



Phase Technology

8005 W. 110th St. | Suite 208

Overland Park, KS 66210

Phone 9136635600

Fax

Toll Free 8556635600

<http://phasetech.mseaudio.com>

All Phase Technologies

products come with a 5-year

limited warranty.