

HV81

8" Down-Firing Subwoofer



Specifications: HV81

Mounting hardware included

Frequency Response (1)	35 Hz - 200 Hz
Max. Program Power	200 W
Max. Continuous Power RMS	100 W
Transducer - Low Frequency Driver	8" Mineral-Filled Poly Cone w/ NBR Surround
Crossover Frequency	50 Hz - 200 Hz Variable; 24 dB/Octave + LFE Setting
Crossover Type	Low Pass
Low Pass Crossover	50 Hz - 200 Hz Variable; 24 dB/ octave + LFE setting
Amp Power	100 W Continuous, 200 W Peak
Colors	Black Ash Laminate
Enclosure alignment	Slot Loaded
Grille - material	Black Cloth
Height (SM = Height)	273.1 mm / 10.75"
Diameter (SM = Width)	355.6 mm / 14"
Depth	406.4 mm / 16"
Weight	11.7 kg / 25.8 lb
Shipping Weight	13.2 kg / 29 lb
Regulatory - CE	approved
Regulatory - RoHS	approved

Description

The HV81 features mica graphite polypropylene drivers, which are extremely rigid yet light enough to produce highly responsive and accurate bass. Its servo controlled amplifier monitors and adjusts its output, allowing for dynamic, undistorted bass.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives

to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Phase Technology

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax
Toll Free 8556635600
<http://phasetech.mseaudio.com>
All Phase Technologies products come with a 5-year limited warranty.

HV81

8" Down-Firing Subwoofer

