

CI-SURR X

6.5" 2-Way In-Wall
Surround Speaker
(Switchable Bipole/Dipole
& Mono/Stereo) With
Micro-Flange Grille



Specifications: CI-SURR X

Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	90 dB
Frequency Response (1)	45 Hz - 20 kHz
Recommended Power	10 - 150 Watts
Transducer - Low Frequency Driver	6.5" Woven Glass Fiber w/ NBR Surround
Transducer - High Frequency Driver	(2) 1" Soft Dome With Level Adjustment
Crossover Type	2-Way Absolute Phase™
Colors	White
Enclosure alignment	Infinite Baffle
Grille - material	White Magnetic Powder-Coated Galvanized Steel Micro-Flange
Height (SM = Height)	319.2 mm / 12.57"
Diameter (SM = Width)	219.2 mm / 8.63"
Depth	95.3 mm / 3.75"
Cutout Height (Surface Mount Height)	288.9 mm / 11.37"
Cutout Width/Diameter	187.3 mm / 7.37"
Mounting Depth	95.3 mm / 3.75"
Weight	2.5 kg / 5.5 lbs
Shipping Weight	2.7 kg / 6 lbs
Accessories Optional	Pre-Construction Bracket (RB-23)
Regulatory - CE	approved
Regulatory - RoHS	approved

CI-SURR X

6.5" 2-Way In-Wall
Surround Speaker
(Switchable Bipole/Dipole
& Mono/Stereo) With
Micro-Flange Grille



Description

The CI-Surround X is the clear choice for Bipole/Dipole surround speaker in a home theater system. It utilizes a dual voice coil woofer with two tweeters.

They can also be combined for two channels of input as a single stereo speaker. The weather resistant design makes it an excellent choice for bathrooms, hot tubs or outdoors.

The CI-Surr X pairs with the entire [Premier Collection](#).

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers

and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH

testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Phase Technology

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax
Toll Free 8556635600
<http://phasetech.mseaudio.com>
All Phase Technologies products come with a 5-year limited warranty.

CI-SURR X

6.5" 2-Way In-Wall
Surround Speaker
(Switchable Bipole/Dipole
& Mono/Stereo) With
Micro-Flange Grille



Optional Accessories

Pre-Construction Bracket (RB-23)