



HS15 PRODUCT SPECIFICATIONS

| | |
|---------------------------|--|
| NOMINAL IMPEDANCE | 8Ω |
| SENSITIVITY dB @ 2.83V/1M | 85 dB |
| FREQUENCY RESPONSE | 120 Hz - 22 kHz |
| RECOMMENDED POWER | 10 - 40 Watts |
| TWEETER | N/A |
| MIDRANGE | N/A |
| WOOFER | 3" (76.2 mm) Polypropylene w/ NBR Surround |
| ENCLOSURE MATERIAL | Injection-Molded ABS |
| ENCLOSURE TYPE | Sealed |
| INPUTS | Terminal Strip |
| GRILLE | Powder-Coated Aluminum |
| COLOR OPTIONS | Black or White |
| DIMENSIONS | 4.35" (110.5 mm) Diameter x 4.35" (110.5 mm) H |
| WEIGHT | 1.4 lbs |
| SHIPPING WEIGHT | 2 lbs |
| INCLUDED ACCESSORIES | Ceiling-Mount Cover Plate, 10' Speaker Signal/ Hanging Cable |
| OPTIONAL ACCESSORIES | N/A |
| REGULATORY - UL | UL 1480 (UEAY) Approved |
| REGULATORY - CE | Approved |
| RoHS | Approved |

Description:

The HS15 is a premium full-range 3 inch pendant-mount speaker. The HS15 incorporates an adjustable 10 foot length of speaker signal/hanging cable for on-ceiling applications. Components are weatherized for indoor/outdoor applications.

The HS15 utilizes the all-in-one ceiling mount system designed to retrofit in most junction boxes. A decorative cover plate is included to hide mounting element and hold excess signal/hanging cable.

Features:

- 3 inch (76.1 mm) polypropylene driver with butyl rubber surround
- Weatherized components for indoor/outdoor applications
- Ultra-low profile ZeroReflection™ ABS enclosure
- Corrosion-resistant, powder-coated aluminum grille
- UL 1480 (UEAY) approved
- Included accessories: Mounting element, cover plate, 10ft speaker signal/hanging cable

Applications:

The HS15 is designed for home audio applications, whether indoors or out, and ideal for finished ceilings where full-range intelligibility, unobtrusive design and installation ease are paramount.

Warranty Information:

The HS15 comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W. 110th Street
Suite 208
Overland Park, KS 66102
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.phasetech.com

Mechanical Drawings

