



Specifications: HV121 II

Mounting hardware included

Nominal Impedance	4 Ω
Frequency Response (1)	22 Hz - 250 Hz
Crossover Frequency	50 Hz - 250 Hz Variable; 24 dB/Octave + LFE Setting
Low Pass Crossover	50 Hz - 250 Hz Variable; 24 dB/Octave + LFE Setting
Amp Power	150 Watts
Colors	Black Textured
Height (SM = Height)	425.5 mm / 16.75"
Diameter (SM = Width)	400.1 mm / 15.75"
SM Depth (Including Bracket)	419.1 mm / 16.5"
Weight	10.91 kg / 24 lb
Shipping Weight	12.73 kg / 28 lb
Regulatory - RoHS	approved

Description

The newly re-designed HV subwoofers bring improved performance and looks to Phase Tech's acclaimed entry-level sub series. The HV121-II is a 12" ported, design that delivers high performance from its single 12" mineral-filled Poly woofer. A full featured 150W integrated amp provides clean and controlled power.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Phase Technology

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax
Toll Free 8556635600
<https://phasetech.mseaudio.com>
All Phase Technologies products come with a 5-year limited warranty.

HV121 II

HV121 II

PHASE[®]
T E C H
