



Specifications: PC 9.5

Mounting hardware included

Nominal Impedance	4 ohms
Sensitivity dB @ 2.83V/1M	91 dB
Frequency Response (1)	28 Hz - 22 kHz
Recommended Power	20 - 450 Watts
Transducer - Low Frequency Driver	6.5" RPF® Flat-Piston Fiberglass & Kevlar Composite Cone w/ NBR Surround
Transducer - High Frequency Driver	1" Patented Synthetic Soft Dome
Colors	High Gloss Black
Enclosure alignment	Ported
Grille - material	Black Cloth, Magnetic
Height (SM = Height)	1155.7 mm / 45.5"
Diameter (SM = Width)	228.6 mm / 9"
Depth	378.4 mm / 14.7"
Weight	30 kg / 66 lb
Shipping Weight	32.7 kg / 72 lb
Regulatory - CE	approved
Regulatory - RoHS	approved

Description

The newest to the Premier Collection, the three-way PC9.5 freestanding tower represents PhaseTech's most advanced technology and design profile, reflecting the value of handcrafted quality". Utilizing three patented 6.5" tri-laminate Kevlar/RPF®/Glass Fiber flat-piston woofers, a 1.5" soft dome midrange, and a 1" soft dome tweeter, the PC9.5 is able to produce an incredibly detailed soundstage in conjunction with its Absolute Phase® Crossovers.

Elegantly curved high-gloss black cabinets make the PC9.5 a stunning addition to any room.

For in-ceiling/in-wall options, pair the PC9.5 with the [CI6.2X](#), [CI7.3X](#), [CI20X](#), [C I60 VIII Kit](#), [CI70X](#), [CI-SURR-X](#), [CI110-SIII](#), [CI120](#), or [CI130](#).

Applications

The PC9.5 is designed for home audio applications.

For in-ceiling and in-wall options, pair the PC9.5 with the CI6.2X, CI7.3X, CI60 VIII Kit, CI70X, CISURRX, CI110 SIII, CI120 or CI130.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit®

software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Feature

- Three 6.5 inch tri-laminate of RPF®, Kevlar and Fiberglass (Patent #4566178) woofers that match the speed and accuracy of the one 1 inch soft dome tweeter
- One 1.5 inch patented synthetic soft dome midrange
- Absolute Phase® Crossover networks ensure that the speaker drivers are acoustically and electronically "in phase" and moving in unison
- Magnetic black cloth grille

PC 9.5

3-Way Tower Speaker



Phase Technology

8005 W. 110th St. | Suite 208

Overland Park, KS 66210

Phone 9136635600

Fax

Toll Free 8556635600

<https://phasetech.mseaudio.com>

All Phase Technologies

products come with a 5-year

limited warranty.