

CI7.3X

8" 3-Way In-Ceiling Speaker With
Micro-Flange Grille



Specifications: CI7.3X

Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	92 dB
Frequency Response (1)	32 Hz - 22 kHz
Recommended Power	15 - 200 Watts
Transducer - Low Frequency Driver	8" Woven Glass Fiber w/ NBR Surround
Transducer - High Frequency Driver	1" Variable Axis Soft Dome With Level Adjustment
Transducer - Full-Range Driver	1.5" Synthetic Soft Dome
Crossover Type	3-Way Absolute Phase™
Colors	White
Enclosure alignment	Infinite Baffle
Grille - material	White Powder-Coated Galvanized Steel Magnetic Micro-Flange (paintable)
Diameter (SM = Width)	244.3 mm / 9.62"
Depth	127.0 mm / 5"
Cutout Width/Diameter	244.5 mm / 9.62"
Cutout Depth	127.0 mm / 5"
Weight	2.7 kg / 6 lb
Shipping Weight	3.2 kg / 7 lb
Regulatory - CE	approved
Regulatory - RoHS	approved

CI7.3X

8" 3-Way In-Ceiling Speaker With
Micro-Flange Grille



Description

The CI7.3X utilizes the same midrange and tweeter technology found in our critically acclaimed Premier Collection PC9.5 speaker. The CI-7.3X three-way design delivers outstanding reproduction of music and movie soundtracks. Signature audio clarity and balance are immediately noticeable from this upscale, virtually invisible speaker.

All CI-X models feature micro flange magnetic grilles, which are paintable. Square grilles are also available for all CI-X in-ceiling models.

The CI7.3X is featured in the EMEA and Global Award Winner installation for [CEDIA Best Home Theatre Awards](#).

The CI7.3X pairs with Premier Collection's [PC3.5](#) and [PC9.5](#).

Applications

Engineered for home theater or distributed audio applications indoors or out (as long as it is not exposed to direct heavy weather). The CI7.3X pairs with PC3.5 and PC9.5.

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit®

software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Features

- Limited Lifetime Warranty
- Auto-Reset Overload Protection
- Absolute Phase Crossover Network
- Offset Tweeter Design
- Magnetic Micro-Flange Grilles

CI7.3X

8" 3-Way In-Ceiling Speaker With
Micro-Flange Grille



Phase Technology

8005 W. 110th St. | Suite
208

Overland Park, KS 66210

Phone 9136635600

Fax

Toll Free 8556635600

[https://phasetech.mseaudi
o.com](https://phasetech.mseaudio.com)

All Phase Technologies
products come with a 5-
year limited warranty.

CI7.3X 8" 3-Way In-Ceiling Speaker With Micro-Flange Grille



Optional Accessories

Pre-Construction Bracket (RB-22)

Square Micro-Flange Grille (CI7X-SG)