



HS26 PRODUCT SPECIFICATIONS

| | |
|---------------------------|-------------------------------------------------------------------------|
| NOMINAL IMPEDANCE | 16Ω |
| SENSITIVITY dB @ 2.83V/1M | 86 dB |
| FREQUENCY RESPONSE | 80 Hz - 22 kHz |
| RECOMMENDED POWER | 10 - 64 Watts |
| TAP SELECTOR | Six-Position Rotary Switch w/ Transformer Bypass Position |
| TWEETER | 1" (25.4 mm) Silk Dome |
| MIDRANGE | N/A |
| WOOFER | 6.5" (165.1 mm) Polypropylene w/ NBR Surround |
| ENCLOSURE MATERIAL | Injection-Molded ABS, Glass Fiber Reinforced |
| ENCLOSURE TYPE | Ported |
| INPUTS | Four-Position Ceramic Terminal Connector |
| GRILLE | Powder-Coated Aluminum |
| COLOR OPTIONS | Black or White |
| DIMENSIONS | 10.08" (256 mm) Diameter x 10.4" (264.2 mm) H |
| WEIGHT | 7 lbs |
| SHIPPING WEIGHT | 9 lbs |
| INCLUDED ACCESSORIES | Hanging Hardware (Cable, Clamps & Fasteners), Weather Plug, Cover Plate |
| OPTIONAL ACCESSORIES | N/A |
| REGULATORY - UL | UL 1480 (UEAY) & 2239 Approved |
| REGULATORY - CE | Approved |
| RoHS | Approved |

Description:

The HS26 features a 6.5 inch high-power coaxial driver with a 1 inch silk dome tweeter. An integrated 70V transformer allows users to operate in a bypass (16 ohm) or transformer mode. The pendant-shaped enclosure is optimized to eliminate standing sound waves and deliver intelligible sound, constructed of injection-molded ABS with glass fiber reinforcement for lasting durability in indoor or outdoor applications. Each model includes hanging hardware with galvanized steel cables and hanging bracket for fast, easy and secure installation.

Features:

- 6.5 inch (165.1 mm) polypropylene driver with butyl rubber surround
- 16 ohm impedance for easy daisy chaining in low voltage systems
- Weatherized components for indoor/outdoor applications
- Ultra-low profile ZeroReflection™ ABS enclosure
- Corrosion-resistant, powder-coated aluminum grille
- Built-in thermal fuse
- UL 1480 (UEAY) & 2239 approved
- High quality black or white paint finish; speaker is paintable
- Included accessories: hanging hardware including 10' cable, clamps & fasteners, weather plug and cover plate

Applications:

The HS26 is designed for home theater audio applications, whether indoors or out, and ideal for finished ceilings where full-range intelligibility, unobtrusive design and installation ease are paramount.

Transformer Options:

| 70.7 V OUTPUT | 100 V OUTPUT | 25 V OUTPUT |
|---------------|---------------|---------------|
| 32 W 104.0 dB | 32 W 104.0 dB | 4 W 95.0 dB |
| 16 W 101.0 dB | 16 W 101.0 dB | 2 W 92.0 dB |
| 8 W 98.0 dB | 8 W 98.0 dB | 1.0 W 89.0 dB |
| 4 W 95.0 dB | 4 W 95.0 dB | 0.5 W 86.0 dB |
| 2 W 92.0 dB | | |

Warranty Information:

The HS26 comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W. 110th Street
Suite 208
Overland Park, KS 66102
Phone: 913.663.5600
Fax: 913.663.3200
Toll Free: 855.663.5600
www.phasetech.com

Mechanical Drawings

