



## PC3.5 PRODUCT SPECIFICATIONS

NOMINAL IMPEDANCE	4Ω
SENSITIVITY dB @ 2.83V/1M	91 dB
FREQUENCY RESPONSE	32 Hz - 22 kHz
RECOMMENDED POWER	20 - 250 Watts
TWEETER	1" (25.4 mm) Patented Synthetic Soft Dome
MIDRANGE	1.5" (38.1 mm) Patented Synthetic Soft Dome
WOOFER	(2) 6.5" (165.1 mm) RPF® Flat-Piston Fiberglass & Kevlar Composite w/ NBR Surround
ENCLOSURE MATERIAL	Black High Gloss Finish on MDF
ENCLOSURE TYPE	Ported
INPUTS	Bi-Wire Gold-Plated 5-Way Binding Posts
GRILLE	Magnetic Black Cloth
COLOR OPTIONS	High-Gloss Hand-Polished Piano Black Finish
DIMENSIONS	22" (558.8 mm) H x 7.9" (180 mm) W x 12.3" (120.7 mm) D
WEIGHT	32 lbs
SHIPPING WEIGHT	38 lbs
INCLUDED ACCESSORIES	Bookshelf Cradle Base
OPTIONAL ACCESSORIES	SST28GB Floor Speaker Stands
REGULATORY - CE	Approved
RoHS	Approved

### Description:

Featuring two patented 6.5" tri-laminate RPF Flat Piston/Kevlar/Fiberglass woofers, a 1" softdome tweeter, and a 1.5" soft dome midrange, the PC3.5 reproduces precise and powerful sound.

The RPF drivers accelerate quickly to high acoustic levels while producing crystal-clear sound at any volume, while simultaneously producing a much larger dispersion pattern. The Absolute Phase® Crossovers expand the resulting "sweet spot" both vertically and horizontally while inhibiting "break up modes".

The PC3.5 has an optional matching speaker stand (SST28GB) that absorbs vibrations while keeping wires hidden from sight.

### Features:

- Two 6.5 inch tri-laminate of RPF®, Kevlar and Fiberglass (Patent #4566178) woofers that match the speed and accuracy of the midrange dome assembly
- Absolute Phase® Crossover networks ensure that the speaker drivers are acoustically and electronically "in phase" and moving in unison
- Rotatable midrange/tweeter assembly for horizontal or vertical positioning
- Magnetic black cloth grille
- Optional accessory: SST28GB speaker stand

### Applications:

The PC3.5 is designed for home audio applications. For a complete home theater, use in conjunction with a PC1.5 and PC Sub Wireless subwoofer.

For in-ceiling and in-wall options, pair the PC3.5 with the CI6.2X, CI7.3X, CI60 VIII Kit, CI70X, CI-SURRX, CI110 SIII, CI120 or CI130.

### Warranty Information:

The PC3.5 comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

### Phase Technology:

8005 W. 110th Street  
Suite 208  
Overland Park, KS 66102  
Phone: 913.663.5600  
Fax: 913.663.3200  
Toll Free: 855.663.5600  
www.phasetech.com