

PC33.5

Dual 5.25" 3-Way LCR/ Center Channel





	PC33.5 PRODUCT SPECIFICATIONS
NOMINAL IMPEDANCE	4Ω
SENSITIVITY dB @ 2.83V/1M	90 dB
FREQUENCY RESPONSE	50 Hz - 22 kHz
RECOMMENDED POWER	20 - 150 Watts
TWEETER	1" (25.4 mm) Patented Synthetic Soft Dome
MIDRANGE	N/A
WOOFER	(2) 5.25" (133.4 mm) RPF® Flat-Piston Fiberglass & Kevlar Composite w/ NBR Surround
ENCLOSURE MATERIAL	Black High Gloss Finish on MDF
ENCLOSURE TYPE	Sealed
INPUTS	Bi-Wire Gold-Plated 5-Way Binding Posts
GRILLE	Magnetic Black Cloth
COLOR OPTIONS	High-Glass Hand-Polished Piano Black Finish
DIMENSIONS	6.9" (175.3 mm) H x 18" (457.2 mm) W x 9.6" (243.8 mm) D
WEIGHT	18.5 lbs
SHIPPING WEIGHT	22 lbs
INCLUDED ACCESSORIES	Bookshelf Cradle Base
OPTIONAL ACCESSORIES	SST28GB Floor Speaker Stand
REGULATORY - CE	Approved
RoHS	Approved

Description:

Featuring two patented 5.25" tri-laminate RPF Flat Piston/Kevlar/Fiberglass woofers, and a 1" softdome tweeter, the PC33.5 reproduces precise and powerful sound.

The RPF drivers accelerate quickly to high acoustic levels while producing crystal-clear sound at any volume, while simultaneously producing a much larger dispersion pattern. The Absolute Phase® Crossovers expand the resulting "sweet spot" both vertically and horizontally while inhibiting "break up modes".

The PC33.5 has an optional matching speaker stand (SST28GB) that absorbs vibrations while keeping wires hidden from sight.

Features:

- Two 5.25 inch tri-laminate of RPF®, Kevlar and Fiberglass (Patent #4566178) woofers that match the speed and accuracy of the one 1 inch soft dome tweeter
- Absolute Phase[®] Crossover networks ensure that the speaker drivers are acoustically and electronically "in phase" and moving in unison
- Horizontal or vertical positioning to perform as an LCR for mains or surrounds
- Magnetic black cloth grille
- · Optional accessory: SST28GB speaker stand

Applications:

The PC33.5 is designed for home audio applications. For a complete home theater, use in conjuction with a PC1.5, PC-Surround II and PC Sub Wireless subwoofer.

For in-ceiling and in-wall options, pair the PC33.5 with the Cl6.1X, Cl6.2X, Cl20X, Cl60 VIII Kit, ClSURRX, Cl110 SIII or Cl150.

Warranty Information:

The PC33.5 comes with a limited ten (10) year warranty. A limited three (3) year warranty comes on all electronics. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W. 110th Street Suite 208 Overland Park, KS 66102

Phone: 913.663.5600 Fax: 913.663.3200 Toll Free: 855.663.5600 www.phasetech.com